

Title	HP1.95	HP1.95Half	HP1.5	HP1.5 Half
Pixel Pitch	1.953mm	1.953mm Half	1.5625mm	1.5625mm Half
LED Configuration	SMD1515	SMD1515	SMD1212	SMD1212
Max Brightness Calibrated	600~750nits	600~750nits	600~750nits	600~750nits
Panel Dimension	500mm x 1000mm x 80mm 19.7" x 39.4" x 3.1"	500mm x 500mm x 80mm 19.7" x 19.7" x 3.1"	500mm x 1000mm x 80mm 19.7" x 39.4" x 3.1"	500mm x 500mm x 80mm 19.7" x 19.7" x 3.1"
Panel Resolution (H x V)	256x512	256x256	320x640	320x320
Weight Per Panel	9kg 19.84lbs	5.2kg 11.44lbs	9kg 19.84lbs	5.2kg 11.44lbs
Power Consumption Max/Average	280W / 84W	140W / 42W	280W / 84W	140W / 42W
Serviceability	Front / Rear	Front / Rear	Front / Rear	Front / Rear
Viewing Angle Vertical	140°	140°	140°	140°
Viewing Angle Horizontal	160°	160°	160°	160°
Refresh Rate	3840Hz	3840Hz	3840Hz	3840Hz
Gray Scale	16bit	16bit	16bit	16bit
Scan Ratio	1/32	1/32	1/20	1/20
Operational Temp/Humidity	-20°C ~ 45°C, 10% ~ 90% HR -4°F ~ 113°F, 10% ~ 90% HR	-20°C ~ 45°C, 10% ~ 90% HR -4°F ~ 113°F, 10% ~ 90% HR	-20°C ~ 45°C, 10% ~ 90% HR -4°F ~ 113°F, 10% ~ 90% HR	-20°C ~ 45°C, 10% ~ 90% HR -4°F ~ 113°F, 10% ~ 90% HR
Storage Temp/Humidity	-40°C ~ 60°C, 10% ~ 90% HR -40°F ~ 140°F, 10% ~ 90% HR	-40°C ~ 60°C, 10% ~ 90% HR -40°F ~ 140°F, 10% ~ 90% HR	-40°C ~ 60°C, 10% ~ 90% HR -40°F ~ 140°F, 10% ~ 90% HR	-40°C ~ 60°C, 10% ~ 90% HR -40°F ~ 140°F, 10% ~ 90% HR
IP Rating	IP30	IP30	IP30	IP30
Use environment	Indoor	Indoor	Indoor	Indoor
Max. Hanging	12 panels	24 panels	12 panels	24 panels
Max. Stacking	6 panels	12 panels	6 panels	12 panels
Input voltage (nominal)	100 V.AC to 240V.AC			
Input power frequency	50 to 60 Hertz			

